

CCR 531
Digital Satellite
HD Receiver
Common Interface
USB PVR ready

CityCom
Communication Systems

CCR 531

CCR 531

DVB-S HD receiver with Common Interface for all digital satellite TV - and radio channels



Receiver

Receiver

Features

- 4000 channel locations for the reception of all digital satellite TV- and radio channels
- DVB-S /DVB-S2 H 2.64 compatible
- 12-character alphanumerical display
- PVR-ready via USB
- Upscaling of the standard TV programmes into the formats 576i/p, 720p and 1080i
- Teletext- and subtitle function
- Favorite lists
- Electronic Programme Guide (EPG)
- Timer function (30 Timer also programmable via EPG, 1 Sleep Timer)
- Comfortable preprogrammed for several satellites
- Fast channel switch
- Connection for an optional external IR sensor
- DiSEqC
- AC3 digital audio out (electrical and optical)
- Comfortable first installation
- Display for signal strength and signal quality
- Software download via PC (RJ11) or Update Over Air (OTA)
- Low power consumption (less than 1W at Standby)
- Infrared remote control

CCR 531
 Digital Satellite
 HD Receiver
 Common Interface
 USB PVR ready

Technical Details

Tuner		
Input frequency	MHz	950 - 2150
Transmission standard		DVB-S/S2
Symbol rate		2 - 45
Impedance	Ohm	75
Chip & Memory		
Processor	MHz	2 x 32 bit RISC CPU
Memory	MBit	2 x 512 DDR RAM
Power supply		
Mains voltage	V	230VAC +/- 10%, 50 - 60 Hz
Standby	W	< 1
LNB-supply	mA	500
Connection		
Tuner input		F-connector
Common Interface		1 x CI slot
Video signal (digital)		HDMI
Video signal (analogue)		2 x SCART
Audio AC3		optical, electrical (RCA)
Serial port		RJ-11
USB		USB 2.0 (max. 700 mA)
General		
Dimensions	mm	370 x 155 x 57
Weight	Kg	ca. 0,8